

# EcoStation™

## EARPLUG DISPENSER WITH SEALED SNAP-IN REFILLS



### EASIEST DISPENSER TO REFILL

### INCREASED COMPLIANCE AND COST SAVINGS

Convenient, quick access and ease of use for more compliance. Plus, workers take only one pair at a time, so there is less waste. Less waste means more cost savings. Economical alternative to packaged earplugs.

### LOW INITIAL INVESTMENT

Competitive earplug dispensers are expensive, cumbersome and sometimes don't even come with earplugs! The EcoStation Starter Pack is a lower cost turnkey solution and comes prefilled with 500 pairs of earplugs. More cost effective than other earplug dispensers.

### SNAP-IN REFILL

Easy to install refill, snaps in quickly, for fast changeover. The sealed refill helps prevent contamination.

### SAVE GREEN & BE GREENER

The refillable and recyclable EcoStation dispenser is easy on the hearing protection budget and easy on the environment. Plus it's 100% PVC-Free like all Moldex products and packaging.



### EARPLUGS EVERYWHERE AND ANYWHERE THEY'RE NEEDED

With the EcoStation, you can afford to put earplugs in all the places they're needed. Hang one near workstations, outside the restrooms, in the breakroom, small spaces, and high traffic locations. Easy, convenient access to hearing protection will ensure that the earplugs are being used and will save time.

### HYGIENIC FROM DISPENSER TO YOUR HAND

Earplugs drop right into the palm of your hand so you don't have to worry about plugs falling on the floor or trays collecting dust and contaminants. When the EcoStation is empty simply dispose of it in the recycle bin and replace with an easy to install refill.

### FEATURES & BENEFITS:

- More economical and green than packaged earplugs
- Easy-to-install, sealed refills, snaps in quickly
- Gives workers easy access to hearing protection
- 500 pairs in each EcoStation
- Compliance – High visibility to increase awareness for your hearing conservation program
- Convenience – Hang a EcoStation anywhere and everywhere plugs are needed
- Cost Savings – Workers take one pair at a time so there are no wasteful grabbing of multiple pairs
- All Moldex hearing protectors are independently tested to ANSI S3.19-1974
- 100% PVC-Free

### AVAILABLE EARPLUGS, 500 PAIR / ECOSTATION



**Softies EcoStation**  
6701 Starter Kit  
6702 Refill  
NRR 33db



**Sparkplugs EcoStation**  
6703 Starter Kit  
6704 Refill  
NRR 33db



**Pura-Fit EcoStation**  
6705 Starter Kit  
6706 Refill  
NRR 33db



**Meteors EcoStation**  
6707 Starter Kit  
6708 Refill  
NRR 33db

**MOLDEX®**  
Ideas that wear well.™



Made in U.S.A.

## EARPLUG DISPENSER WITH SEALED SNAP-IN REFILLS

PART # / DESCRIPTION	DISPLAY	CASE
6701 Softies Starter Kit	500 Pairs	4 Dispensers
6702 Softies Refill	500 Pairs	4 Dispensers
6703 SparkPlugs Starter Kit	500 Pairs	4 Dispensers
6704 SparkPlugs Refill	500 Pairs	4 Dispensers
6705 Pura-Fit Starter Kit	500 Pairs	4 Dispensers
6706 Pura-Fit Refill	500 Pairs	4 Dispensers
6707 Meteors Starter Kit	500 Pairs	4 Dispensers
6708 Meteors Refill	500 Pairs	4 Dispensers
6868 PlugStation/EcoStation Magnetic Bracket Assembly	1 Bracket/ 1 Envelope	1 Envelope



6868

### WARNING TO USER

1. Use these laboratory derived attenuation data for comparison purposes only. The amount of protection afforded in field use often is significantly lower depending upon how the protectors are fitted and worn.
2. Failure to obtain a proper fit will reduce effectiveness of hearing protectors and could result in hearing loss or injury.
3. Over protection can be dangerous. The wearer must be able to hear warning signals.
4. Wearers with hearing loss should exercise extreme caution.
5. It is the employer's responsibility to ensure that the type of hearing protector and its rating is appropriate for the user in their particular workplace.
6. Failure to follow all instructions and warnings could result in increased risk of hearing loss, serious injury or death.
7. Moldex earplugs must only be used as part of a hearing conservation program that complies with applicable local safety and health regulations.

### MOLDEX TECHNICAL ASSISTANCE

Moldex provides all of the technical assistance required to set up a hearing protection program. For more information call +1 (800) 421-0668 or +1 (310) 837-6500 ext. 512/550 or E-mail: tech@moldex.com or visit [www.moldex.com](http://www.moldex.com).

Keep earplugs away from infants and small children as they may get caught in the windpipe and create a choking hazard.



**MOLDEX®**  
Ideas that wear well.™

**MOLDEX-METRIC, INC.**  
10111 Jefferson Blvd.  
Culver City, CA 90232  
TEL: +1 (800) 421-0668 or  
+1 (310) 837-6500  
FAX: +1 (310) 837-9563  
E-mail: sales@moldex.com  
[www.moldex.com](http://www.moldex.com)

**CANADIAN CUSTOMER SERVICE**  
Tel: +1 (800) 421-0668, Ext. 550/510  
Fax: +1 (310) 837-9563

### ATTENUATION DATA OF SOFTIES

Tested According to ANSI Specs S3.19-1974 Michael & Assoc., State College, PA.  
Probado de acuerdo a las especificaciones ANSI S3.19-1974 Michael & Assoc., State College, PA.  
Tests Conformes aux Spéc. ANSI S3.19-1974 Michael & Assoc., State College, PA.

Frequency (Hz) Frecuencia (Hz) Fréquence (Hz)	125	250	500	1000	2000	3150	4000	6300	8000	NRR 33	CSA AL
Mean Attenuation (dB) Atenuación de Dato (dB) Atténuation Moyenne (dB)	42.3	43.7	46.6	40.9	38.6	44.7	46.9	49.3	48.3		
Standard Deviation (dB) Desviación Standard (dB) Écart Standard (dB)	5.0	6.0	5.8	4.2	2.8	3.2	3.3	4.2	3.6		

### ATTENUATION DATA OF SPARKPLUGS

Tested According to ANSI Specs S3.19-1974 by Michael & Assoc., State College, PA.  
Probado de acuerdo a las especificaciones ANSI S3.19-1974 Michael & Assoc., State College, PA.  
Tests Conformes aux Spéc. ANSI S3.19-1974 Michael & Assoc., State College, PA.

Frequency (Hz) Frecuencia (Hz) Fréquence (Hz)	125	250	500	1000	2000	3150	4000	6300	8000	NRR 33	CSA AL
Mean Attenuation (dB) Atenuación de Dato (dB) Atténuation Moyenne (dB)	42.3	43.7	46.6	40.9	38.6	44.7	46.9	49.3	48.3		
Standard Deviation (dB) Desviación Standard (dB) Écart Standard (dB)	5.0	6.0	5.8	4.2	2.8	3.2	3.3	4.2	3.6		

### ATTENUATION DATA OF PURA-FIT

Tested According to ANSI Specs S3.19-1974 by Michael & Assoc., State College, PA.  
Probado de acuerdo a las especificaciones ANSI S3.19-1974 Michael & Assoc., State College, PA.  
Tests Conformes aux Spéc. ANSI S3.19-1974 Michael & Assoc., State College, PA.

Frequency (Hz) Frecuencia (Hz) Fréquence (Hz)	125	250	500	1000	2000	3150	4000	6300	8000	NRR 33	CSA AL
Mean Attenuation (dB) Atenuación de Dato (dB) Atténuation Moyenne (dB)	42.4	43.5	45.9	39.8	36.8	44.5	46.6	48.1	47.4		
Standard Deviation (dB) Desviación Standard (dB) Écart Standard (dB)	4.9	4.2	4.9	3.4	2.0	3.7	2.9	4.6	4.7		

### ATTENUATION DATA OF METEORS

Tested According to ANSI Specs S3.19-1974 by Michael & Assoc., State College, PA.  
Probado de acuerdo a las especificaciones ANSI S3.19-1974 Michael & Assoc., State College, PA.  
Tests Conformes aux Spéc. ANSI S3.19-1974 Michael & Assoc., State College, PA.

Frequency (Hz) Frecuencia (Hz) Fréquence (Hz)	125	250	500	1000	2000	3150	4000	6300	8000	NRR 33	CSA AL
Mean Attenuation (dB) Atenuación de Dato (dB) Atténuation Moyenne (dB)	40.7	42.3	41.8	41.2	39.4	45.9	46.3	47.4	47.4		
Standard Deviation (dB) Desviación Standard (dB) Écart Standard (dB)	5.2	5.1	4.5	3.5	3.2	3.8	4.3	3.8	4.3		

### DISTRIBUTED BY:



Printed on Recycled Paper